













Dimension	100*75*45mm (W*D*H)
Print method	Line thermal printer
Paper width	58mm
print width	48mm
Weight (g)	205g
Max diameter of paper roll	40mm
Dot per lie	384 dots/line
Print speed	90mm/s
Life cycle time	50km(printing density under 12.5%)/100million pulses
text and graphic Support	English, figure, symbol, Graph, curve, iconprestored, barcode (CODE39EAN13EAN8 CODABARCODE128CODE93ITF)
Dot pitch (resolution)	203DPI/8 dots/mm
interface	RS232/Mini USB Bluetooth support android and IOS
Power	2000mAh 7.4V rechargeable Lithium battery
Recharge adapter	Stand by recharging / AC adapter
Self-check	Without paper /low power/ cover open
commands	ESC/POS compatible with order sets
Black mark test	Supported
Paper cut	By hands
Operate setting	Temperature:-10°C~50°C; Humidity:20%~85%
Recharge Setting	Temperature:5°C~40°C; Humidity:20%~85%
Storage Setting	Temperature:-20°C~70°C; Humidity:5%~95%
Standard accessories	Long-term Preservable paper, AC adapter, li- ion battery
Optional accessories	Serial interface cable / leather coat



info@udyamasoftware.com 🔾 7414005555





www.udyamasoftware.com