

THERMAL RECEIPT PRINTER



PARAMETER

Basic Configuration

Dimension	111*124*48mm (W*D*H)
Print method	Line thermal Printer
Paper width	80mm Print width : 72 mm
Weight (g)	320g
Max Diameter of paper Roll	45mm
Dot per time	576 dots/line
Print Speed	80mm's
Life Cycle time	50km(printing density under 12.5%) 100 million pluses
Text & Graphic Support	English, Figure, symbol chinese Graph, curve, icon pre-stored, barcode (CODE39EAN13EAN8 CODABARCODE128CDE93ITF)
Dot Pitch (resolution)	203DPI/8 dots/mm
Interface	RS232/Mini USB bluetooth Support android and ios
Power	2600mAh 7.4V rechargeable Lithium Battery
Recharge adapter	Stand by recharging / AC adapter
self-check	without paper / low power / cover open
Commands	ESC/POS compatible with order sets
Black Mark test	Supported
paper cut	Tear bar
Operate-setting	Temperature 10°C~50°C; Humidity: 20%~85%
Recharge Setting	Temperature 5°C~40°C; Humidity: 20%~85%
Storage Setting	Temperature 20°C~70°C; Humidity: 5%~95%
Standard Accessories	Long Tem Preservable Paper, AC adapter , USB cable
Optional accessories	Serial interface cable / leather coat



info@udyamasoftware.com



7414005555



www.udyamasoftware.com